

# **FOODLUBE SUGAR DISSOLVING FLUID**

LPS® FOODLUBE Sugar Dissolving Fluid is a food grade lubricating release agent that rapidly dissolves and removes sugars from application surfaces to ensure components remain fully operational. It leaves a light, durable film on the surface to protect against corrosion and resist further sugar build up.

FOODLUBE Sugar Dissolving Fluid is NSF® H1 registered for incidental contact with food making it ideal for use in food and beverage industries with stringent hygene standards.



010 V LO INF (1)NSE V

\* Only applicable for trigger and 1 gal sizes



## PACKAGE SIZES

Net Contents	Part No.
15 wt.oz. / 425 g/ 427 mL aerosol	57716
28 fl.oz (828 mL) trigger spray	57728
1 gal. (3.78 L)	57701

## **APPLICATIONS**

- Animal feed sugar residue
- Chains on flow wrapping equipment
- Conveyors
- Cutters or blades
- Sugar packaging lines
- Sugar processing lines
  - Weighting plates

## FEATURES

- Rapidly dissolves and removes sugars and fondants from applications commonly found in food and beverage facilities.
- Leaves a light, durable lubricating film on the surface to prevent new accumulations of sugar.
- Provides short term corrosion protection on exposed metal surfaces.
- FOODLUBE Sugar Dissolving Fluid offers a wide temperature resistance of 41°F to 203°F (+5°C to +95°C).
- NSF<sub>®</sub> Registered H1.
- Metal & x-ray detectable plastic components (see back for more details)

### SPECIFICATIONS AND APPROVALS

#### Approved/Qualified to:

- FOODLUBE Sugar Dissolving Fluid is manufactured from only FDA listed ingredients: FDA Group 21 CFR 178.3570
- NSF<sub>®</sub> H1 Registration # 147495 (aerosol)
- NSF<sub>®</sub> H1 Registration # 147492 (bulk)

## **PROPERTIES**

Appearance/Physical State	Liquid
Odor	Mild
Specific Gravity (water=1)	1.00 - 1.10 @ 20°C
VOC Content	Aerosol: 4% Bulk: Not Applicable
Color	Colorless
Flash Point °F (°C)	Aerosol: -118°C (-180°F) TCC propellant Bulk: >302°F (> 150°C)
Chemical Base	Water/Polymer Solution
рН	9.0 - 10.0

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE : WWW.LPSLABS.COM

Sugar build-up on fasteners

## METAL & X-RAY DETECTABLE PLASTIC COMPONENTS (PATENT PENDING)

LPS<sup>®</sup> is a leading food-grade MRO chemical manufacturer that developed the innovative technology, DETEX<sup>TM</sup>, to help reduce the risk of foreign object contamination during food and beverage processing. All DETEX<sup>TM</sup> components on LPS<sup>®</sup> food industry products are metal and x-ray detectable.

	FEATURES	BENEFITS
	All plastic components are metal and x-ray detectable and are capable of detection by most metal detection equipment.	Reduce concerns of food product contamination and assist with HACCP requirements.
(() DETEX+())	All DETEX™ plastic component ingredients are GRAS listed (Generally Recognized As Safe - FDA 21 C.F.R. Sections 177 and 178).	Meets FDA requirements as an acceptable material for use in food processing plants.
Scan to see DETEX™	LPS® food safe maintenance chemicals have prominently displayed NSF® category labeling. This ensures only food safe products are used for maintenance during processing.	Distinct labeling helps to prevent use of non $NSF_{\otimes}$ approved LPS^ products in the food processing area.
in action!	Aerosol can is in compliance with the Food Safety Net Services (FSNS). FDA 21 C.F.R.175.300, 1935/2004/EC.	Aerosol can does not contain: Heavy metals, BADGE, BFDGE, NOGE, and Bisphenol-A (BPA).

Universal blue color for all metal and x-ray detectable plastic components easily identifies them as a non-food object.

Nozzle

Metal Pin



#### ADDITIONAL AEROSOL FEATURES:

- Certified food safe container
- Dual language labeling: English and Spanish
- 2-piece aerosol can; 10% 15% lighter than a 3-piece aerosol can

COMPONENT	DRY MODE	WET MODE
Actuator	2.2 mm	2.5 mm
Сар	3.0 mm	> 3.0 mm

DRY MODE

> 3.0 mm

> 3.0 mm

> 3.0 mm

#### GALLON CAP

COMPONENT

Cap + Metal Liner

Cap Only

Liner Only

#### ADDITIONAL GALLON CAP FEATURES:

- Metal detectable dual language labeling c container: English and Spanish
  - Label adhesive compliant with FDA 175.105

WET MODE

> 3.0 mm

> 3.0 mm

> 3.0 mm

	Trigger Piston Closure
AD	DITIONAL TRIGGER SPRAYER FEATURES:
•	Adjustable spray stream to ensure proper application
•	Ergonomic, 3 finger trigger to reduce finger fatigue
•	Chemically resistant trigger
•	Metal detectable dual language label on container: English and Spanish

TRIGGER SPRAYER

Label adhesive compliant with FDA 175.105

	COMPONENT	DRY MODE	WET MODE
	Whole Sprayer *	> 3.0 mm	> 3.0 mm
	Body	> 3.0 mm	> 3.0 mm
on	Trigger	> 3.0 mm	> 3.0 mm
105	Closure	> 3.0 mm	> 3.0 mm
105	Metal Pin	2.5 mm	> 3.0 mm
	Nozzle	2.5 mm	> 3.0 mm
	Piston	2.0 mm	2.5 mm

 Internal trigger components are not manufactured with DETEX<sup>™</sup> technology and may not be metal or x-ray detectable.

NOTE

 Detection limits for a particular machine depend on a variety of factors including line speed, contaminant placement and orientation, iron fortification (i.e.; flour), wet mode vs. dry mode, fragment size, aperture size, etc. It is the responsibility of the end-user to determine the detection limits of the appropriate DETEX<sup>TM</sup> component for the individual line set up and for the particular food product being inspected.

2. Metal and x-ray detection limits for plastic components (above) are based on whole components. Partial components may not be detectable due to detector limitations, partial component size, malfunctioning equipment and/or the type of food product undergoing processing.

3. LPS® Laboratories recommends that all components be tested prior to implementation (separately and included in the processed food product) and/or consult your specific metal detector equipment manufacturer directly.

- 4. Product shelf life, warranty, and material safety data sheets are available at www.lpslabs.com. LPS® Laboratories is not responsible for use of this product inconsistent with its instructions and warnings.
- 5. LPS<sup>®</sup> Laboratories is not responsible for failure to detect components due to detector limitations and/or detector malfunctions. Refer to the metal detector manufacturer's design limitations, instructions, and warnings regarding the use, limitations, and proper maintenance of the equipment.

LPS® Laboratories • An Illinois Tool Works Company 4647 Hugh Howell Road • Tucker, GA 30084 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899 Internet Web Site: www.lpslabs.com

©2013 LPS® Laboratories • LPS® and DETEX<sup>TM</sup> are registered trademarks of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #TDS\_57716 • Rev. 7/2013



	Revision Date	e: October 17, 2012	Supersedes:	None
	Section	1 • Product and Company Ide	entification	
Product Name:	LPS® FOODL	UBE Sugar Dissolving Fluid (Aerosol	)	
Part Number(s):	57716			
Chemical Name:	Water / Polym	ner Solution		
Product Use:	A sugar disso	lving solution		
Manufacturer Information:	LPS Laborato	ries, 4647 Hugh Howell Road, Tucker	, GA, USA 30084	
	TEL:	USA & Canada: 1 800 241-8334		
		Outside USA and Canada: +1 770	) 243-8800	
	FAX:	USA & Canada: 1 800 543-1563		
		Outside USA and Canada: +1 770	) 243-8899	
Emergency Telephone Number:	Chemtrec:	USA & Canada: 1 800 424-9300		
		Outside USA and Canada: +1 703	3 527-3887	
Website:	http://www.lps	labs.com		
Section 2 • Hazards Identification				

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

	GHS Hazard Level	GHS Hazard Level	Hazard Statement
Signal Word:	Flammable Aerosols	2	H223 - Flammable aerosol.
	Skin Corrosion / Irritation	3	H316 - Causes mild skin irritation.
DANGER			
GHS Symbols:			
	Pred	cautionary Statement	s
Prevention		ven after use. Protect	g. Do not spray on an open flame or other ignition source. from sunlight. Do not expose to temperatures exceeding 50 51, P410, P412, P264]
Response	IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice / attention. Take off contaminated clothing and wash before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF SWALLOWED: Immediately call a POISON CENTER or a doctor / physician. Rinse mouth. Do not induce vomiting. [P302, P352, P332, P313, P362, P305, P351, P338, P304, P340, P301, P310, P330, P331]		
Storage	Protect from sunlight, store in a well-ventilated P412]	place and do not expo	ose to temperatures exceeding 50oC/ 122oF. [ P410, P403,



		<b>Revision Date:</b>	October 17, 201	2	Supersedes:	None
Disposal	Dispose of content	s/container in accordance	e with local / regional	/ national regulations.	[P501]	
Potential Chronic	Health Effects:					
Carcinogenic Effe	ects: NTI	P: No	IARC: No	OSHA: No	ACGI	H: No
Mutagenic Effects	s: None					
Teratogenic Effect	cts: None					
Target Organs:	None					

#### Medical conditions aggravated by exposure:

Persons with pre-existing central nervous system (CNS) disease, neurological conditions, skin disorders, chronic respiratory diseases, or impaired liver or kidney function should avoid exposure.

#### Signs and Symptoms

Stinging in eyes. Repeated or prolonged skin contact can cause redness, irritation, and scaling of the skin (dermatitis). Breathing of high vapor concentrations may cause headaches, stupor, irritation of throat and eyes, and kidney effects.

	Section 3 • Composition	n / Information on Ingredients	i
	Component	CASRN	Weight Percent
	Liquified Petroleum Gas	68476-86-8	2 - 3%
	Sorbitan monolaurate, ethoxylated	9005-64-5	1 - 2%
	Section 4 • F	First Aid Measures	
Eyes:	Check for and remove contact lenses. If irritation or rec minutes. Hold eyelids apart to ensure complete irrigatic immediately.		· · · ·
Skin:	Remove contaminated shoes and clothing. Clean affec medical attention if irritation persists.	ted area thoroughly with mild soap and	l water. DO NOT use ointments. Seek
Inhalation:	Immediately move victim to fresh air. If victim is not bre cardiopulmonary resuscitation (CPR). If breathing is dif	<b>0</b>	
Ingestion:	DO NOT induce vomiting unless directed to do so by m spontaneous vomiting is about to occur, place victim's head down. DO NOT leave victim unattended. Seek me	head below knees. If victim is drowsy o	· ·



	Revision Date:	October 17, 2012	Supersedes:	None
	Sectio	on 5 • Fire Fighting Measures		
Products of Combustion:	Carbon monoxide a	and carbon dioxide.		
General Fire Hazards:		rgized equipment. High heat will cause f closed containers.	e product to boil, evolving	vapor that could cause
Firefighting media:	LARGE FIRE: Use	DRY chemical powder. CO2, water spray, fog or foam. Cool auto-ignition or explosions.	containing vessels with w	ater jet in order to prevent
Sensitivity to Impact:	None	Sensitivity to Static Discharge:	Yes	
Protection Clothing (Fire):	apparatus to protect	se full bunker gear including NIOSH-a ct against potential hazardous combus fight the fire from a maximum distanc	tion or decomposition pro	oducts and oxygen deficiencies.

#### Special Remarks on Explosion Hazards:

Aerosols may explode upon heating, spread fire and overcome sprinkler systems.

	Sec	tion 6 • Accidental Release Measures	
Containment Proce	edures: Small Spill and Leak:	Eliminate ignition sources. Absorb with an inert material and dispose of properly.	
	Large Spill and Leak:	Eliminate ignition sources. Secure the area and control access. Dike far ahead of a liquid spill to ensure complete collection. Pick up free liquid for disposal using absorbent pads, sand, or other inert non-combustible absorbent materials. Place into appropriate waste containers for later disposal.	
Clean-Up Procedu	res: Recover free product and	place in a suitable container for disposal.	
Evacuation Proced	Jures: Ventilate area of leak or sp	pill. Keep unnecessary and unprotected people away.	
Special Procedure	s: Remove all sources of ign	Remove all sources of ignition. Ventilate area. Wear personal protective equipment during cleanup.	
		Section 7 • Handling and Storage	
Handling:	DO NOT spray into or around ignition adequate ventilation. Avoid breathing	sources. After handling, always wash hands thoroughly with soap and water. Use only with vapors or spray mists.	
Storage:	torage: Keep container closed and in a cool, well-ventilated area. Avoid all sources of ignition (spark or flame). Store below 120°F (49°C).		

#### Precautions to be taken in handling and storage:

Store aerosols as Level 1 Aerosol (NFPA 30B). Store all materials in a dry, well-ventilated area. Avoid breathing vapors.



Revision Date:
October 17, 2012
Supersedes:
None

Section 8 • Exposure Controls / Personal Protection
Version 10, 2012

#### Exposure Guidelines:

Component	CASRN	OSHA	ACGIH	NIOSH	Supplier
Sorbitan monolaurate, ethoxylated	9005-64-5	5 mg/m3 (oil mist) PEL	5 mg/m3 (oil mist) TLV	5 mg/m3 (oil mist) TLV	Not established
			10 mg/m3 (oil mist) STEL	10 mg/m3 (oil mist) STEL	Not established
Liquified Petroleum Gas	68476-86-8	1000 ppm PEL	1000 ppm TLV	1000 ppm TWA	None reported

Engineering Controls: Provide general and/or local exhaust ventilation to keep exposures below the exposure guidelines listed above.

#### Personal protective equipment

Eye protection:	Safety glasses with side shields conforming to appropriate regulations. Eye wash fountain and emergency shower facilities are recommended.
Hand protection:	Normally no hand protection is required; however, if product will be sprayed for an extended period, "overspray" onto skin may occur. If so, wear chemical resistant gloves conforming to appropriate regulations. Please observe the instructions regarding permeability and breakthrough time that are provided by the supplier of the gloves.
Respiratory protection:	Typical use of this product under normal conditions does not require the use of respiratory protection. If airborne concentrations are above the applicable exposure limits (listed above), use NIOSH approved respiratory protection (i.e. organic vapor cartridge).
General Hygiene	Wash thoroughly after handling. Have eye-wash facilities immediately available.

Considerations:

#### Section 9 • Physical and Chemical Properties

	,		
Appearance:	Liquid	Color:	Clear, colorless
Odor:	Mild / None	Evaporation Rate:	1 (H2O = 1)
Solubility Description:	Soluble in water	Flash Point:	-118ºC (-180ºF) - propellant
Initial boiling point and	> 100°C (212ºF)	Flash Point Method:	Tag-Closed Cup
boiling range Specific Gravity (H2O=1):	1.00 - 1.10 @ 20°C	Decomposition Temperature:	Not established
Vapor Density (air = 1):	> 1	Auto ignition temperature:	Not established
Vapor Pressure:	<1.00 mm Hg @ 20⁰C	Flammable limits (estimated):	LOWER: N.E. UPPER: N.E.
Rule 1171 PPc:	Not applicable	Partition Coefficient (octanol/water):	< 1



V.O.C. Content:	Aerosol: Aerosol:	Revision Date: 4% Not applicable	October 17, 2012 Odor Threshold:	Supersedes: None Not established		
Melting Point:	Not establi	ished	Viscosity:	Not established		
pH:	9.0 - 10.0		Volatiles:	>80%		
Heat of combustion:		Not applicable Not established				
Section 10 • Stability and Reactivity						
Chemical Stability:	Product is stable under recommended storage conditions.					
Conditions to Avoid:	Keep away from heat and ignition sources. Avoid exposure to direct sunlight for extended periods and temperatures in excess of 122°F (50°C).					
Incompatibility:	Extremely reactive or incompatible with oxidizing agents.					
Hazardous Decomposition:	Combustion will generate smoke, possibly thick and choking, resulting in zero visibility and combustion products include carbon monoxide and carbon dioxide.					
Hazardous Polymerization:		Will not occur.				

#### Section 11 • Toxicological Information

#### Acute and Chronic Toxicity

#### **A: General Product Information**

An acute toxicity study of this product has not been conducted. Information given in this section relates only to individual constituents contained in this preparation.

#### **B: Component Analysis**

Component	CASRN LC-		LD-50
Sorbitan monolaurate, ethoxylated	9005-64-5	Not established	> 5000 mg/kg / oral / rat
Solbitan monolaulate, ethoxylated	9003-04-5	Not established	3000 mg/ kg/ skin / rabbit
Liquified Petroleum Gas	68476-86-8	658 mg/L / rat / 4 hr*	Not appropriate

\* Supplier Data

#### Section 12 • Ecological Information

Mobility:	Non-volatile. Absorbed only slowly into soil	I. Persistence / Degradability:	Only slightly biodegradable
Bioaccumulative potential:	No bioaccumulation potential	Other adverse effects:	See below

The mixture is not classified as environmentally toxic.



**Revision Date:** 

October 17, 2012

Supersedes: None

Ecotoxicity

Effects on Organisms	Component	CASRN	Test	Species	Results
Acute Toxicity on Fishes	Sorbitan monolaurate, ethoxylated	9005-64-5	96-hr LC50	Leuciscus idus	340 mg/L
Acute Toxicity on Daphnia	Sorbitan monolaurate, ethoxylated	9005-64-5	48-hr EC50	Daphnia magna	> 10 mg/L*
Bacterial Inhibition	No data available				
Growth inhibition of algae	Sorbitan monolaurate, ethoxylated	9005-64-5	48-hr EC50	Unspecified Algae	100 mg/L
Bioaccumulation in fish	No data available				

\* Supplier Data

	Section 13 • Disposal Considerations					
Waste Status:	Aerosol cans, if depressurized and emptied to less than 1 inch (2.54 cm) of fluid contents, are classified as non-hazardous waste under 40 CFR 261.7 (U.S.). If disposed of in its received form, the aerosol product carries the waste codes D001 and D003 (U.S.).					
Disposal:	Waste must be disposed of in accordance with any and all applicable environmental control rules and/or regulations.					
Note:	Chemical additions to, processing of, or otherwise altering this material may make this waste management information inaccurate, incomplete, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive than federal laws and regulations.					

#### Section 14 • Transport Information

	Shipping Name:	Aerosols	UN No.:	1950
D.O.T. Ground	Hazard Class:	2.1	Technical Name:	NA
D.O.T. Ground	Subclass:	NA	Hazard Label:	LTD QTY
	Packing Group:	NA		
	UN No.:	1950	ADR Class:	2
Road/Rail -	Packing Group:	NA	Classification Code:	5F
ADR/RID	Name and description:	AEROSOLS, flammable	Hazard ID No.:	NA
	Labeling:	2.1	Technical Name:	NA
	UN No.:	1950	Class:	2
	Shipping Name:	Aerosols	Subsidiary Risk:	2.1
IMDG-IMO	Labeling:	2	Packing Group:	NA
	Packing Instructions:	P003, LP02	EmS:	F-D, S-U
	Marine pollutant:	No	Technical Name:	NA
	UN No.:	1950	Class:	2.1
	Shipping Name:	Aerosols, flammable	Subclass:	NA
IATA - ICAO:	Packing Instructions:	203, Y203 (Ltd. Qty.)	Packing Group:	NA
	Labeling:	Flammable Gas	Technical Name:	NA

The preceding information is subject to change and must be verified prior to shipment. It is the responsibility of anyone offering hazardous materials for shipment to ensure compliance with all applicable regulations.



<b>Revision Date:</b>	October 17, 2012	Supersedes:	None
Section	15 • Regulatory Information		

#### **U.S. Federal Regulations**

RCRA Hazardous Waste No.: D001, D003

Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA): None

#### Toxic Substances Control Act (TSCA):

All components of this product are TSCA inventory listed and/or are exempt.

Superfund Amendments and Reauthorization Act (SARA) Title III SARA Section 311/312 (40 CFR 370) Hazard Categories: Sudden Release of Pressure, Fire Hazard, Immediate (Acute) Health Hazard

This product contains the following toxic chemical(s) subject to reporting requirements of SARA Section 313 (40 CFR 372): None

Section 112 Hazardous Air Pollutants (HAPs): None

#### State Regulations

California: This product does not contain chemical(s) known to the State of California to cause cancer, birth defects or other reproductive harm.

California and OTC States: This product conforms to consumer product regulations.

#### New Jersey Right to Know:

Water 7732-18-5 • EO/PO polymer 9003-11-6 • Liquified Petroleum Gas 68476-86-8 • Decanedioic acid, disodium salt 17265-14-4 • Propylene Glycol 57-55-6 • Sorbitan monolaurate, ethoxylated 9005-64-5

Bulk: Not applicable

#### International Regulations

Montreal Protocol listed ingredients:	None
Stockholm Convention listed ingredients:	None
Rotterdam Convention listed engredients:	None
RoHS Compliant:	Yes



		Revision Date:	October 17, 20		
		Sectio	on 16 • Otner	Information	
MODO	457740	HMIS III		NFPA	
MSDS#:	157716			Flammability	
MSDS Preparation		Health:	[/] 1	•	
Responsible Name:			[/] '		
Elena Badiuzzi		Flammability Aerosol:	2	Health	
Compliance Manager		Flammability Bulk:	NA		
Telephone: +1 770 243-8800		Physical Hazard Aerosol:	2	$\sim$	
		Physical Hazard Bulk:	NA	Special	

#### Notice to Reader:

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Ed Williams, Technical Manager LPS Laboratories, a division of Illinois Tool Works